



- UNPOLISHED STONE AND AGGLOMERATES
- CONCRETE
- MANUFACTURED STONE



WHAT IT'S FOR

- Protects outdoor floors from water and damp
- Makes walls and coverings water-repellent.
- Ideal for cement
- Protects grout joints
- Protects against deterioration due to weather conditions

ADVANTAGES

- It provides a breathable, lasting and renewable protection
- Does not affect the material's natural look
- Does not yellow with ageing or with any environmental condition
- High penetration capacity
- It has high coverage
- Prevents moss and mould formation
- It protects against efflorescence

HOW TO USE IT

No dilution required: ready to use.

Application:

Apply evenly with a large flat paintbrush on perfectly clean and dry surface. On vertical surfaces spray the product (airless system), taking care to use the correct volume.

You can apply the product once or twice, depending on the absorbing capacity of material, waiting 24 hours between one coat and the next. Apply one coat on low-absorbency natural stones (such as slate), and two coats on more absorbent natural stones or on cement. For outdoor surfaces where oil-repellent qualities are also required, after 24 hours apply a finishing coat of FILAFOB.

Maintenance:

diluted solution of FILACLEANER

Caution:

On natural stone carry out a patch test on a small surface area to check for any changes in colour.

Do not apply the product externally if rain is forecast.

COVERAGE

With one litre:

Absorbent stone	10/20 m ²
Concrete	5 m ²

"Coverage shown is for guidance purposes only and refers to single coats"

Packaging

1-litre cans in boxes of 12.

5-litre cans in boxes of 4.

WARNINGS

- Keep out of reach of children.
- Do not disperse into the environment after use.
- It does not protect marble and limestone from acid.
- The use of a single-disc cleaning machine is permitted only if it is perfectly undamaged.

Outdoor flooring must be properly laid before being treated and must satisfy all specific requirements, including: adequate sloping, properly executed expansion joints, perfect insulation from underlying ground, proven compatibility with sub-zero temperatures.

TEMPERATURES

Storage temperature: from 0° to 30°C

The product should be applied to materials with temperature between 5° and 30° C.

COMPOSITION

- A mixture of siloxane compounds dispersed in de-aromatised hydrocarbon solvent.

LABELLING

Warning: Danger

Hazard indication:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking.

Caution recommendations:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. Dispose of contents / container in accordance with official regulations. Contains: NAPHTHA (PETROL.) HYDROTREATED HEAVY



TECHNICAL FEATURES

Appearance: liquid

Colour: colourless

Odour: slight hydrocarbon solvent smell

Density: 0.777 kg/l

Flash point: 40 °C

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring.

Fila shall not accept any responsibility for improper use of its products.