

FILALONGLIFE

GLOSSY PROTECTIVE WAX



- TERRACOTTA
- QUARRY TILES
- SLATE
- STONE AND AGGLOMERATES
- RUBBER AND PVC
- LAMINATE FLOORING
- LINOLEUM
- RESIN



WHAT IT'S FOR

- Protects floors subjected to high traffic.
- Ideal for protecting unpolished natural stone, granite and terracotta floors.
- Generates a high-gloss and ultra-protective polymer surface film.
- Ideal for protecting polished natural stone floors in public areas.
- Perfect on floors of resilient type (rubber, PVC...)

ADVANTAGES

- No need to polish.
- High adhesion capacity.
- Easy application.
- Can be undiluted or diluted as necessary.
- Maintenance can be carried out using a single-disc cleaning machine at high speed.

HOW TO USE IT

For protecting surfaces
Apply a coat of product evenly and continuously to a clean dry floor, using a fleece pad, cloth or other applicator. Wait 1 hour. Then apply a second coat at right angles to the first. When dry, the floor will shine without requiring polishing.

If treating highly absorbent natural stone (limestone, sandstone, terracotta), we recommend a base coat of FILAFOB or FILAW68. Wait 24 hours before applying FILALONGLIFE.

For maintenance:
Restoring sheen (every 2-3 months): after cleaning the surface with a diluted solution of FILACLEANER (1:200), apply FILALONGLIFE diluting 500 ml of product in 5 litres of water. The floor can be walked on once it is dry.

Restoring protection (once a year): remove wax from the surface using FILAPS87 detergent diluted 1:5. Rinse. Apply FILALONGLIFE to the dry and clean floor undiluted, using a fleece pad or other applicator. The floor can be walked on once it is dry.

COVERAGE

With one litre:

Terracotta	30 m ²
Stone	30/40 m ²
Rubber/PVC, plastic laminates, Linoleum, Resin (undiluted)	30 m ²
Rubber/PVC, plastic laminates, Linoleum, Resin (diluted 1:10)	300 m ²

"Coverage shown is for guidance purposes only and refers to single coats"

Caution:

Do not walk on floor while it's drying and do not repeat application on treated areas which are not yet dry.

To remove this wax, use the specific wax-remover FILAPS87.

The use of Filalonglife on rustic ground terracotta should be assessed each time depending on the characteristics of the terracotta.

Not recommended for use on outdoor surfaces or in damp environments and where water remains (bathrooms, showers).

Packaging

1 litre cans in boxes of 12.

5-litre cans in boxes of 4.

WARNINGS

- Keep out of reach of children,
- Do not disperse into the environment after use.

TEMPERATURES

Storage temperature: from 5° to 30° C
The product must be applied to material with a temperature of between 10° and 30°C.

COMPOSITION

Aqueous emulsion of metallic polymers, polyethylene waxes, wetting resins, plasticisers, perfume and additives (preservative and anti-foam agent).

LABELLING

No safety and risk labelling or instructions are required, as the product is not classified as hazardous under current regulations.

TECHNICAL FEATURES

Appearance: liquid
Colour: milky white
Odour: fresh fragrance
Density: 1.035 kg/l
pH: 8.6

This information is the result of our most up-to-date technical know-how and is based on ongoing laboratory research and testing. Nevertheless, for reasons beyond our control, any suggestions always require appropriate analysis, testing and monitoring. Fila shall not accept any responsibility for improper use of its products.

REV. 00 - 08/05/2014